

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



D6

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 2000356752 A

(43) Date of publication of application: 26.12.00

(51) Int. Cl. G02B 26/10
B23K 26/00
B23K 26/08
// G01R 5/00
G05D 3/12

(21) Application number: 11169611

(22) Date of filing: 16.06.99

(71) Applicant: MATSUSHITA ELECTRIC IND CO LTD

(72) Inventor: MEGA HIRONAO
KASAI KENJI
SATO HIROKAZU

(54) GALVANOMETER CONTROLLER

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a galvanometer controller which is provided with a rotational position correcting means capable of correcting the fluctuated portion of the characteristic of a position sensor quickly and highly accurately by a simple means in which the applying of fabrication is not necessary actually to a material to worked.

SOLUTION: In this galvanometer controller, when a correction mode is set when a fluctuation is generated in the output signal of a position sensor 9 by receiving the effect of environmental change or the like, a position instruction generating means 1 outputs a position instruction signal rotating a galvanometer 8 to a position where it is brought into contact with a mechanical limiter. When an instructed position by the position instruction signal at the point of time when the limit position of the galvanometer 8 is detected is different from a relational expression, the means 1 in which an arithmetic means 6 performs an operation changing the relational expression so as to correspond to the

fluctuated portion of the sensor 9 outputs the position instruction signal of the instructed position which is calculated based on the relational expression changed by the means 6.

COPYRIGHT: (C)2000,JPO

